

曜岩應用材料有限公司

Midas Applied Materials Corporation

TECHNICAL DATA SHEET

Barium Titanate

鈦 酸 鋇

Chemicals

Properties		Unit	Index
Ba/Ti [mol ratio]		%	0.997
Sodium	[Na]	≦ ppm	10
Calcium	[Ca]	≦ ppm	10
Iron	[Fe]	≦ ppm	20
Potassium	[K]	≦ ppm	10
Manganese	[Mn]	≦ ppm	10
Strontium	[Sr]	≦ ppm	150

Physicals

Properties		Unit	Index
Particle size		um	0.1
Sp.surface area		m²/g	-
Ignition loss (1100°C/1 hr)		≦ %	1.58
Crystallinity			Cubic
Particle size distribution	[D ₁₀]	um	0.36
	[D ₅₀]	Um	0.42
	[D ₉₀]	um	0.47

PACKAGING

Packed in 25 kg plastic drum

CAS No # 12047-27-7

The information herein is believed to be reliable. However no warranty, express or implied is made as to its accuracy or completeness and none is made as to the fitness of this material for any purpose. The manufacturer shall not be liable for damages to person or property resulting from its use. Nothing herein shall be construed as a recommendation for use in violation of any patent. Consult the Material Safety Data Sheet for additional information.